



Part	Part no.
1 Railings	See table
2 Single bracket	UG1000
3 Double bracket	UG2000
4 Washer	UL4201
5 Bolt M10x20	BU1201/BU1200
6 Flange nut M10	MU1001/MU1010

Part	Part no.
7 Kick strip	SL0410/SL0510/SL0710/SL1010/SL1510/SL2010
8 Self-drilling screw 5.5x22	SS5221/SS5225
9 Gull wing connection	MK4200
10 Tube coupling	KP4277

The edge distance applies for M12 expander in concrete




Railing	c/c measurement
UI2042 / UB2042	1845
UI1542 / UB1542	1345
UI1042 / UB1042	845
UI0742 / UB0742	545
UI0542 / UB0542	345
UI0442 / UB0442	245




### 1. Installation of bracket

Screw the brackets (2,3) using 4 attachments (A) per bracket.  
**NB** Attachments are NOT included.




### 2. Installation of railing lock

Fit a nut (6) + lock washer (4) on a railing lock. Insert the railing tube and fit a bolt (5).



### 3. Installation of kick strip

Any kick strip (7) is to be fitted using 2 self-tapping screws (8).



### 4. Installation of couplings

Install a gullwing coupling (9) or tube coupling (10) between the railings.