

Guarantee for the surface treatment of roof safety products

Weland Stål guarantees the service life of the surface treatment on all standard products in normal environments and with the prescribed maintenance.

Hot-dip galvanised steel in accordance with SS-EN ISO 1461	60 years
Stainless steel	60 years
Copper	60 years
Magnelis	30 years
Powder-coated	30 years

Conditions

The owner of the material must be able to verify it was purchased from Weland Stål with the help of a delivery note or invoice.

Normal environment means corrosivity class C4 (Atmosphere with marked air pollutant levels or with moderate salt levels, industrial and coastal areas).

The installation must have been carried out according to the installation instructions that applied at the time of installation.

Any metal filings must be removed immediately. Damage to the surface treatment that arising during installation must be touched up with suitable paint.

Scope

The guarantee covers standard products that are sold after 1 January 2015.

Weland Stål has the right to carry out inspections on site before the claim is approved.

Weland Stål replaces damaged parts with new material delivered cost free to the assembly site.

Weland Stål has the right to carry out the replacement work with its own or contracted personnel.

Maintenance of roof safety products

According to the Planning and Building Act (PBL) and the Act on Technical Requirements for Construction Works, inspections of roof safety devices must be carried out regularly. **Weland Stål recommends this be done annually.**

The purpose of the inspection is to detect faults and/or deficiencies that may arise due to weather, other damage or inadequate installation.

Inspection points

- The safety devices have been installed in accordance with Weland Stål's assembly instructions.
- When supplementing individual roof safety installations, do not mix parts from different manufactures.
- Deformed and/or damaged safety devices/fastenings must be replaced.
- Any paint damage on the products has to be touched up.
- Snow guards, roof gangways and roof ladders, where there is a risk for overloading due to snow, must be unloaded by clearing the snow.