

## Product Sheet - Guardrail round Climbing Hatch

### The product's unique identification code

Part no.	Name	Part no.	Name
BF3000	Adjustable fixing concrete tile	TP1722	Fixing plate universal c/c 170-220 mm
FF0300	Integrated standing seam mount installed	TP3551	Sealing plate raised 25 mm 350x520 mm
FF0430	Standing seam mount for snap-on sheet	TP3552	Sealing plate smooth 350x520 mm
FP0300	Base plate 300x100 mm		
FP1030	Base plate smooth		
FP3000	Footplate adjustable mount		
FP3010	Footplate adjustable mount - High		
IP33XX	Fixing profile, L=330		
IP5000	Fixing profile		
LF3310	Lath bracket		
ML5002	Angle-iron backing plate, L=500mm		
NS5000	Bracket type 5, plain roofs		
RB0010	Hoop		
RR2712	Railing tube 27 mm length 1.2m		
RR2730	Railing tube 27 mm length 3m		
SF0600	Quick fixing mount L=60mm		
SF1350	Quick fixing mount L=135mm		
SR5001	Guardrail corner baluster		
SR5002	Guardrail baluster		
TF3000	Adjustable fixing clay tile		
TP1217	Fixing plate universal c/c 120-170 mm		

### Identification of construction product

All products can be identified and traced by means of stamped part no. and date marking, alternatively by reference to drawing.

### The construction product's intended use

Permanently installed guardrails enabling the anchoring of personal fall protection equipment

### The manufacturer's name and contact details

<b>Manufactur</b>	Weland Stål AB	<b>Telephone</b>	0321-261 60
<b>Address</b>	Industrivägen 1 SE-523 90 Ulricehamn	<b>E-mail</b>	<a href="mailto:info@welandstal.se">info@welandstal.se</a>
		<b>Internet</b>	<a href="http://www.welandstal.se">www.welandstal.se</a>

### Inspection of the performance of the construction product

Testing

#### Inspection body

SP, Technical Research Institute of Sweden, no. 0402  
SP issued approval certificate 103601.

### Stated performance

Essential characteristics	Performance	Technical specification
Mechanical strength	Static loading acc. 5	SS 83 13 33:2014
Mechanical strength	Dynamic loading acc. 5	SS 83 13 33:2014
Design	Acc. 5	SS 83 13 33:2014
Durability	At least C3 for 15 years acc. 6	SS 83 13 33:2014

The products listed above agree with the stated performance as reported in the document.  
This Declaration of Performance has been issued on the sole authority of Weland Stål AB

Signed for Weland Stål AB  
Ulricehamn, 12/04/2016



Klas Gunnarsson, Quality Manager

